

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - en



perma Liquid grease SF06

Version	Revision Date:	Date of last issue: 11.04.2019	Print Date:
1.4	21.11.2019	Date of first issue: 20.01.2015	21.11.2019

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name : perma Liquid grease SF06

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-
stance/Mixture : Grease

Recommended restrictions
on use : Restricted to professional users.

1.3 Details of the supplier of the safety data sheet

perma-tec GmbH & Co. KG
Hammelburger Str. 21
97717 EUERDORF
GERMANY
Tel: +49 9704 609-0
Fax: +49 9704 609-50
info@perma-tec.com

E-mail address of person
responsible for the SDS : msds@perma-tec.com

National contact : H-T-L perma UK
6 – 9 The Square
Stockley Park
UXBRIDGE
MIDDLESEX UB11 1FW
UNITED KINGDOM
Phone: +44 20 8622 3076
Fax: +44 20 8622 3200
www.perma-tec.com

1.4 Emergency telephone number

+49 9704 609-99 (Mo-Do 08:00-16:30, Fr 08:00-12:00)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Long-term (chronic) aquatic hazard, Category 3 H412: Harmful to aquatic life with long lasting effects.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - en



perma Liquid grease SF06

Version	Revision Date:	Date of last issue: 11.04.2019	Print Date:
1.4	21.11.2019	Date of first issue: 20.01.2015	21.11.2019

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard statements : H412 Harmful to aquatic life with long lasting effects.

Precautionary statements : **Prevention:**
P273 Avoid release to the environment.

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature : Mineral oil.
aluminium complex soap

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration limits M-Factor Notes	Concentration (% w/w)
2-(2-heptadec-8-enyl-2-imidazolin-1-yl)ethanol	95-38-5 202-414-9 01-2119777867-13-XXXX	Acute Tox.4; H302 Skin Corr.1C; H314 Eye Dam.1; H318 STOT RE2; H373 Aquatic Acute1; H400 Aquatic Chronic1; H410	M-Factor: 10/1	>= 0.25 - < 1
N-methyl-N-[C18-(unsaturated)alkanoyl]glycine	701-177-3 01-2119488991-20-XXXX	Acute Tox.4; H332 Skin Irrit.2; H315 Eye Dam.1; H318 Aquatic Acute1; H400	M-Factor: 1/	>= 0.25 - < 1

For explanation of abbreviations see section 16.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - en



perma Liquid grease SF06

Version	Revision Date:	Date of last issue: 11.04.2019	Print Date:
1.4	21.11.2019	Date of first issue: 20.01.2015	21.11.2019

SECTION 4: First aid measures

4.1 Description of first aid measures

- If inhaled : Remove person to fresh air. If signs/symptoms continue, get medical attention.
Keep patient warm and at rest.
If unconscious, place in recovery position and seek medical advice.
Keep respiratory tract clear.
If breathing is irregular or stopped, administer artificial respiration.
- In case of skin contact : Remove contaminated clothing. If irritation develops, get medical attention.
Wash off with soap and water.
Wash clothing before reuse.
Thoroughly clean shoes before reuse.
- In case of eye contact : Rinse immediately with plenty of water, also under the eyelids, for at least 10 minutes.
If eye irritation persists, consult a specialist.
- If swallowed : Move the victim to fresh air.
If unconscious, place in recovery position and seek medical advice.
Keep respiratory tract clear.
Do not induce vomiting without medical advice.
Never give anything by mouth to an unconscious person.

4.2 Most important symptoms and effects, both acute and delayed

- Symptoms : No information available.
- Risks : None known.

4.3 Indication of any immediate medical attention and special treatment needed

- Treatment : No information available.
-

SECTION 5: Firefighting measures

5.1 Extinguishing media

- Suitable extinguishing media : Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.
- Unsuitable extinguishing media : High volume water jet

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - en



perma Liquid grease SF06

Version	Revision Date:	Date of last issue: 11.04.2019	Print Date:
1.4	21.11.2019	Date of first issue: 20.01.2015	21.11.2019

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : Fire may cause evolution of: Carbon oxides

5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus. Use personal protective equipment. Exposure to decomposition products may be a hazard to health.

Further information : Standard procedure for chemical fires. Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Evacuate personnel to safe areas.
Use the indicated respiratory protection if the occupational exposure limit is exceeded and/or in case of product release (dust).
Do not breathe vapours, aerosols.
Refer to protective measures listed in sections 7 and 8.

6.2 Environmental precautions

Environmental precautions : Do not allow contact with soil, surface or ground water.
If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Clean up promptly by sweeping or vacuum.
Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Avoid contact with skin and eyes.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Wash hands and face before breaks and immediately after handling the product.
Do not ingest.

